

Color Dispersion Instruction Sheet

One Day Floors

Description:

One Day Floors™ Color Dispersions are pigments designed to add color to the One Day Floor coatings. Because they are packaged by themselves, Color Dispersions reduce inventory levels. Color Dispersions allow varying levels of opacity to the One Day Floors™ sealer by varying the amount of concentrated pigment that is added to the A component of the One Day Floor™ coatings product. Color Dispersions are used to create opaque “safety net” backgrounds for media floors like chips and quartz floor systems. Color Dispersions may also be used to color concrete floors in solid opaque fashion or to create translucent appearances.

Mixing:

Add 9 ounces of Color Dispersion per one gallon of part A for an opaque appearance. Add 2 to 5 ounces for a translucent appearance. Add more pigment to create more opacity and less to create more translucence. Carefully monitor the amount of Color Dispersion added to each gallon for the appropriate opacity level. After mixing the Color Dispersion into part A mix thoroughly with part B for 60 seconds. To insure uniformity from batch to batch, monitor the amount of Color Dispersion carefully.

Safety:

Avoid skin contact, use eye protection. Do not ingest. Dispose of in accordance with all local, state and federal laws.

Keep out of reach of children!

NON-Warranty: The information herein is based upon the best information available at the time of printing. Data provided is intended for those having skill and ability to use products recommended in a safe and responsible manner. LIABILITY is limited to the cost of material proven to be defective. There is no warranty expressed or implied as related to any issue which is deemed to be a direct result of improper surface preparation or cleaning, application over concrete or cementitious surfaces which have not reached full cure, those having excessive rising moisture/vapor or hydrostatic pressure, application over surfaces which have previously been sealed without first testing for compatibility/adhesion, adverse water conditions, acts of God or acts of others, constant submersion in harsh environments, workmanship or applicator, or any other cause and effect which is not related to defective material.

Distributed by:

CIMARRON

125 NE 40th St.

Oklahoma City, OK 73105

Toll free: 1-866-906-2006

Fax: 405-526-2008